

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

PORTIONS OF THE SOUTH (FIFTH STANDARD PARALLEL SOUTH), EAST, WEST, AND  
NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 1, 2, 3, 4, 8, 9, 10, 15, 18, 19, 20, 21, 24,  
27, 28, 29, 30, 31, 32, 33, AND 34,

IN

TOWNSHIP 25 SOUTH, RANGE 10 WEST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

***Scott A. Burkhardt***  
***Cadastral Surveyor***

Under Special Instructions dated and approved ***May 29, 2012***, which provided  
for the surveys included under Group No. ***1196***, and Assignment Instructions  
dated ***May 29, 2012***.

Survey Commenced, ***June 5, 2012***  
Survey Completed, ***June 27, 2012***

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

PORTIONS OF THE SOUTH (FIFTH STANDARD PARALLEL SOUTH), EAST, WEST, AND  
NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 1, 2, 3, 4, 8, 9, 10, 15, 18, 19, 20, 21, 24,  
27, 28, 29, 30, 31, 32, 33, AND 34,

IN

TOWNSHIP 25 SOUTH, RANGE 10 WEST,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

***Scott A. Burkhardt***  
***Cadastral Surveyor***

Under Special Instructions dated and approved ***May 29, 2012***, which provided  
for the surveys included under Group No. ***1196***, and Assignment Instructions  
dated ***May 29, 2012***.

Survey Commenced, ***June 5, 2012***  
Survey Completed, ***June 27, 2012***

# INDEX DIAGRAM

TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

6	16 5	15 35 4	14 28 3	13 23 2	19 1 7
12 7	47 46 8	34 33 9	27 26 10	22 21 11	19 18 12
45 11 18	44 44 17	33 32 16	26 24 15	21 20 14	13 17
43 11 19	42 41 20	32 31 21	22	23	24 6 16
40 10 30	40 38 29	30 29 28	24 27	26	25 5
38 8 31	37 36 32	28 33 4	24 23 34	35	36

Subdivision of section 1.....	Page 47
Subdivision of section 2.....	Page 48
Subdivision of section 3.....	Page 49
Subdivision of section 4.....	Page 50
Subdivision of section 8.....	Page 51
Subdivision of section 9.....	Page 52
Subdivision of section 10.....	Page 54
Subdivision of section 15.....	Page 55
Subdivision of section 18.....	Page 55
Subdivision of section 19.....	Page 57
Subdivision of section 20.....	Page 58
Subdivision of section 21.....	Page 60
Subdivision of section 24.....	Page 61
Subdivision of section 27.....	Page 62

Subdivision of section 28.....	Page 64
Subdivision of section 29.....	Page 65
Subdivision of section 30.....	Page 65
Subdivision of section 31.....	Page 68
Subdivision of section 32.....	Page 72
Subdivision of section 33.....	Page 73
Subdivision of section 34.....	Page 75

## TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes describe the dependent resurvey of portions of the south (Fifth Standard Parallel South), east, west, and north boundaries, a portion of the subdivisional lines, and the subdivision of sections 1, 2, 3, 4, 8, 9, 10, 15, 18, 19, 20, 21, 24, 27, 28, 29, 30, 31, 32, 33, and 34, in T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

## HISTORY OF SURVEYS

Surveyed by		Retr. or Resurveyed by	
<b>SOUTH BOUNDARY (Fifth Standard Parallel South)</b>			
All	J. Bausman	1870	
Portion		J.W. Dougall	1911
Portion		M.J. Kurchinski	2011-12
<b>EAST BOUNDARY</b>			
All	J. Bausman	1870	
All		A.J. Stewart Jr.	1882
<b>WEST BOUNDARY</b>			
All	J. Bausman	1870	
Portion		L.V. Judd	2001
<b>NORTH BOUNDARY</b>			
All	J. Bausman	1870	
Portion		L.V. Judd	2001
<b>SUBDIVISION</b>			
All	J. Bausman	1870	
Portion		L.V. Judd	2001

## PRIVATE AND COUNTY SURVEYS

A copy of all of these plats will be kept with the Cadastral Survey Group File for this survey.

A survey described as "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL" was performed by James D. Edwards, Utah Registered Professional Land Surveyor No. 162522, recorded at the Millard County Recorder's Office on October 8, 2008 under Serial No. 00171125.

A survey represented on the "RECORD OF SURVEY MAP for CIRCLE FOUR REALTY", in Townships 25 and 26 South, Range 9 West, was made by Douglas B. Grimshaw, Utah Registered Professional Land Surveyor No. 174457, Grimshaw Surveying, Inc., signed and stamped on June 23, 1997, and filed at the Millard County Recorder's Office as plat No. 140 on September 4, 1997.

A survey represented on the "MILLARD COUNTY SECTION CORNER SURVEY", in Township 24 South, Range 10 West, was made by Kary B. Monroe, Utah Registered Professional Land Surveyor No. 6295, Jones and DeMille Engineering, signed and stamped on December 10, 1992, , filed at the Millard County Recorder's Office.

## TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

An unrecorded survey described as "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM" was performed by James D. Edwards, Utah Registered Professional Land Surveyor No. 162522, Westwood Professional Services, dated September 20, 2011, prepared for Milford Wind Farm, was obtained from Edwards Surveying, Inc.

An unrecorded plat, "CERTIFICATE OF SURVEY" prepared for Milford Wind Corridor, by Scott A. Gyllen, Utah Registered Land Surveyor No. 6763499, Westwood Professional Services, Inc., located in Townships 25, 26, and 27 South, Ranges 9, 10, and 11 West, was obtained from Westwood Professional Services, Inc.

MILLARD COUNTY SURVEYORS SECTION TIES are kept on file at the County Recorder's Office. These documents are filed independently of any record of survey plat and reflect county contracts with Registered Land Surveyor's to recover and/or reestablish Public Land Survey System monuments with Global Positioning System observations and physical rehabilitation.

## TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group No. 1196, dated May 29, 2012.

The direction of each line is with reference to the true meridian, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the *Standards For the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems (GNSS)*, dated February 23, 2009. Trimble model R8 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Geodetic control was derived from GPS static observations, post processed by National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): DL6904 NVSV SPRING VALLEY CORS ARP, DM7135 NVPI PIOCHE CORS ARP, and DI2242 P009 MARYSVALE\_UT 2006 CORS ARP.

The geographic position for the corner of sections 1, 2, 35, and 36, on the north boundary of T. 25 S., R. 10 W., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **38°40'28.863" N.**,  
Longitude: **112°56'05.336" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,  
Network Accuracy = 0.200 meter at 95% confidence.

The geographic position for the corner of sections 1, 6, 31, 36, Tps. 25 and 26 S., Rs. 10 and 11 W., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: **38°35'14.281" N.**,  
Longitude: **113°01'41.328" W.**, N.A.D. 83 (2011), EPOCH: 2010.00,  
Network Accuracy = 0.200 meter at 95% confidence.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
 (FIFTH STANDARD PARALLEL SOUTH),  
 TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

Dependent Resurvey of a Portion of the South Boundary  
 (Fifth Standard Parallel South),  
 T. 25 S., R. 10 W., Salt Lake Meridian, Utah

---

The Reestablishment of the Survey Executed by J. Bausman in 1870  
 and the Resurvey executed by M.J. Kurchinski 2011-12

---

Beginning at the standard 1/4 section corner of sections 4 and 33, Townships 25 and 26 South, Range 10 West, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 15 inches above the ground, with aluminum cap, 3 inches diameter, marked as described in the official record of the 2011-12 resurvey, with a rebar, 1/2 inch diameter, projecting 1 inch above the ground, with yellow plastic cap, marked EDWARDS 162522 alongside; and with a wood post, 4 inches square, projecting 4 1/2 feet above the ground, alongside.

Corner lies in a fenceline, 4-strand barbed-wire, wood posts, extending east and west.

**N. 89°43.7' W.**, between sections 4 and 33.

**20.456** Point for the W 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
                   S33  
 W 1/16             
                   S4  
                   T26S  
                   2012

Set a steel fence post north of the corner.

Corner is located in gently-rolling, sandy ground, west of the westerly Union Pacific Railroad right-of-way fence extending north and south.

**32.300** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

**40.912** The corner of sections 4, 5, 32, and 33, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with aluminum cap marked as described in the official record of the 2011-12 resurvey.

With a steel fence post west of the corner.

---

From the corner, an aluminum rod, 1 inch diameter, firmly set, projecting 4 inches above ground, bears S. 89°48.0' E., 0.568



DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY  
(FIFTH STANDARD PARALLEL SOUTH),  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

chains distance, with aluminum cap, 3 inches diameter, marked MILLARD COUNTY SURVEY LS 162522 T25S R10W 32 33 5 4 T26S. Not utilized in this resurvey.

Corner is located on level ground in a low lying dry slough of the Beaver River bottoms, with tamarisk trees.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J. Bausman in 1870, and the Dependent Resurvey Executed by A.J. Stewart Jr. in 1882

---

From the 1/4 section corner of sections 25 and 30, monumented by Douglas B. Grimshaw, as shown on "RECORD OF SURVEY MAP FOR CIRCLE FOUR REALTY" dated June 23, 1997 on file at the Millard County Recorder's Office, monumented with a rebar, 1/2 inch diameter, buried 4 inches below the surface of an improved gravel road, determined latitudinally by proportionate measurement and longitudinally by a fenceline, 4-strand barbed-wire and wood posts, extending South from a fence corner, a juniper post, 5 inches diameter, projecting 7 feet above the ground, bearing S. 0°19.9' W., 36 links distance from the rebar. There is no remaining evidence of the 1870 wood post, which was reset in the 1882 resurvey; there is no remaining evidence of an aluminum rod, 1 inch diameter with aluminum cap, 3 inches diameter, set by James D. Edwards in 2008, as shown on "MILLARD COUNTY SURVEYORS SECTION TIES" dated May 5, 2008, on file at the Millard County Recorder's Office, Page No. 126-5. This position is accepted as the best available evidence of the original corner position.

This rebar is not remonumented.

From which the new reference monuments set here

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 29 inches in the ground, with magnet at base, for a reference monument, bears N. 42°59.3' E., 30.4 links distance, with aluminum cap marked RM T25S R9W S30 20.1 FT. TO COR. 2012 and an arrow pointing to the corner. Set a steel fence post north of aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 28 inches in the ground, with magnet at base, for a reference monument, bears N. 38°24.0' W., 28.9 links distance, with aluminum cap marked RM T25S R10W S25 19.1 FT. TO COR. 2012 and an arrow pointing to the corner. Set a steel fence post north of aluminum post.

From the aforementioned fence corner, a fence, 4-strand barbed-wire with wood posts, also extends east.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°05.6' E., between sections 25 and 30.

- 40.252 The corner of sections 19, 24, 25, and 30, monumented with a limestone, 23 x 15 x 6 inches, firmly set, projecting 10 inches above the ground, with 2 notches on the south edge, 4 notches on the north edge (Record: 18 x 12 x 8 inches); with a mound of stone, 2 feet diameter, 1 foot high, east of the corner.

At the corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T25S	
R10W	R9W
S24	S19
S25	S30

2012

Bury original marked stone southeast of the corner.

Rebuild mound of stone, 2 feet diameter, one foot high, east of the corner.

Set a steel fence post north of the corner.

Corner is located in gently-rolling ground, with grasses.

N. 0°01.7' E., between sections 19 and 24.

- 40.219 The 1/4 section corner of sections 19 and 24, monumented by Douglas B. Grimshaw, as shown on "RECORD OF SURVEY MAP FOR CIRCLE FOUR REALTY" dated June 23, 1997 on file at the Millard County Recorder's Office, monumented with a rebar, 1/2 inch diameter, projecting 4 inches above the ground, with remains of a plastic cap, determined by proportionate measurement. There is no remaining evidence of the 1870 wood post, or the 1882 marked stone. This position is accepted as a careful and faithful reestablishment of the original corner position.

At the corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S	
R10W	R9W
1/4	
S24	S19

2012

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Place rebar in aluminum post.

Set a steel fence post west of the corner.

Corner is located in fairly level, open ground, with grasses.

---

N. 0°01.6' E., beginning new measurement.

- 40.219** The corner of sections 13, 18, 19, and 24, monumented with a limestone, 34 x 14 x 7 inches, firmly set, projecting 5 inches above the ground, with 3 notches on the north edge, 3 notches on the south edge (Record: 30 x 12 x 8 inches), with a steel fence post east of the corner. There is no remaining evidence of the 1882 witness mound of stone.

At the corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S	
R10W	R9W
S13	S18
S24	S19

2012

Bury original marked stone west of the corner.

Corner is located in fairly-level, open ground, with grasses.

---

From the corner of sections 1, 6, 7, and 12, monumented with an unrecorded rebar, 5/8 inch diameter, firmly set, projecting 2 inches above the ground, with yellow plastic cap, 1 inch diameter, partially destroyed, marked PLS (?)152671; there is no remaining evidence of the 1870 wood post, which was reset in the 1882 resurvey. This position is accepted as a careful and faithful reestablishment of the original corner position.

At the corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T25S	
R10W	R9W
S1	S6
S12	S7

2012

Place rebar in aluminum post.

Set a steel fence post south of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located in fairly-level, open ground, with grasses.

N. 0°01.1' W., between sections 1 and 6.

- 40.252 Point for the 1/4 section corner of sections 1 and 6, at proportionate distance. There is no remaining evidence of the 1870 wood post, which was reset in the 1882 resurvey.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S  
R10W R9W  
1/4  
S1 | S6  
2012

Set a steel fence post east of the corner.

Corner is located in fairly-level, open ground, with grasses.

- 80.504 The corner of Townships 24 and 25 South, Ranges 9 and 10 West, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, in a mound of stone, 2 feet diameter, 1 foot high, with aluminum cap, marked SURVEY MARKER 1992 T24S R10W R9W S1/S6/S31/S36 T25S LS 6295 RESTORED BY MILLARD COUNTY, with a stone, not of record, 12 x 12 x 6 inches, firmly set, projecting 5 inches above the ground, with 6 notches on one edge, 6 notches on another edge, incorporated in the mound of stone. There is no remaining evidence of the 1870 wood post, which was reset in the 1882 resurvey. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Bausman in 1870

---

From the corner of Townships 25 and 26 South, Ranges 10 and 11 West, monumented with an iron post, 3 inches diameter, firmly set in concrete, projecting 2 inches above the ground, with brass cap marked as described in the official record of the 2011-2012 resurvey, with a steel fence post west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

The rusted remains of a portion of the 1911 iron post and remains of wood posts and lath are scattered on ground near corner.

Corner is located on level, open ground, with greasewood and grasses.

N. 0°16.2' E., between sections 31 and 36.

20.112 Point for the S 1/16 section corner of sections 31 and 36. Not monumented.

40.224 The 1/4 section corner of sections 31 and 36, monumented by James D. Edwards, as shown on an unrecorded survey "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM", dated September 20, 2011, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 4 inches above the ground, with aluminum cap, 3 inches diameter, marked incorrectly MILLARD COUNTY SURVEY T25S R10W 1/4 36/31 2008 LS 162522, with a cut wood post, 2 x 3 inches in diameter, 2 feet long, with no visible markings, lying loose next to corner; there is no remaining evidence of the 1870 wood post. This position is accepted as a careful and faithful reestablishment of the original corner position.

Set a steel fence post north of the corner.

From the corner, a rebar, 1/2 inch diameter, firmly set, projecting 1 inch above the ground, bears S. 23°16.5' E., 25.3 links distance, with aluminum cap, 1 1/2 inches diameter, marked LAPS E263P L64E RLS 3322. This unrecorded monument was not utilized in the course of this resurvey.

---

N. 0°16.1' E., beginning new measurement.

20.113 Point for the N 1/16 section corner of sections 31 and 36. Not monumented.

40.226 The corner of sections 25, 30, 31, and 36, monumented by James D. Edwards, as shown on an unrecorded survey "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM", dated September 20, 2011, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 5 inches above the ground, with aluminum cap, 3 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 25/30/31/36 R11W 2008 LS 162522. With an angle iron set flush in the ground alongside, and an old, weathered wood post, 2 x 5 inches in diameter, 4 feet long, with no visible markings, lying loose next to corner. There is no remaining evidence of the 1870 wood post. This position is accepted as the best available evidence of the original corner position.

Set a steel fence post north of the corner.

Corner is located on fairly level, open ground, with desert

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

brush.

N. 0°24.3' E., between sections 25 and 30.

20.215 Point for the S 1/16 section corner of sections 25 and 30. Not monumented.

40.430 Point for the 1/4 section corner of sections 25 and 30, at proportionate distance. There is no remaining evidence of the position of the 1870 wood post. A wood post, 2 x 3 inches in diameter, 2 feet long, with no visible markings, was lying loose on the ground nearby.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S  
R11W R10W  
1/4  
S25 | S30  
2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with scattered blackbrush.

60.645 Point for the N 1/16 section corner of sections 25 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S  
R11W R10W  
N 1/16  
S25 | S30  
2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with scattered blackbrush.

80.860 Point for the corner of sections 19, 24, 25, and 30, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S  
R11W R10W  
S24 | S19  
S25 | S30  
2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with scattered blackbrush.

N. 0°24.3' E., between sections 19 and 24.

- 40.430** Point for the 1/4 section corner of sections 19 and 24, at proportionate distance. There is no remaining evidence of the position of the 1870 wood post. The remnants of an old wood post, 3 feet long, with no visible markings, lying loose on the ground nearby, and another wood post, 2 x 4 inches in diameter, 2 1/2 feet long, with one sharpened end, marked S ? 1/4, lying loose on the ground nearby.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S  
R11W R10W  
1/4  
S24 | S19  
2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with blackbrush.

- 60.645** Point for the N 1/16 section corner of sections 19 and 24. Not monumented.
- 80.860** The corner of sections 13, 18, 19, and 24, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2001 resurvey. There are several remnants of wood posts, various diameters and lengths, with no visible markings, lying loose on the ground nearby.

Set a steel fencepost east of the corner.

Reestablishment of the Survey Executed by J. Bausman in 1870  
and the Retracement Executed by L.V. Judd in 2001.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

N. 0°03.0' E., between sections 13 and 18.

- 40.261 Point for the 1/4 section corner of sections 13 and 18, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S  
R11W R10W  
1/4  
S13 | S18  
2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with blackbrush.

- 80.522 Point for the corner of sections 7, 12, 13, and 18, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, in a collar of stone, 2 feet diameter, with aluminum cap marked

T25S  
R11W R10W  
S12 | S7  
S13 | S18  
2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with desert brush.

N. 0°03.0' E., between sections 7 and 12.

- 40.261 Point for the 1/4 section corner of sections 7 and 12, at proportionate distance. There is no remaining evidence of the position of the 1870 wood post. There are several remnants of wood posts, various diameters and lengths, with no visible markings, lying loose on the ground nearby.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked



DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S  
R11W R10W

1/4

S12 | S7

2012

Set a steel fence post north of the corner.

Corner is located in fairly-level, open ground, with desert brush.

- 80.522** The corner of sections 1, 6, 7, and 12, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 7 inches above the ground, with aluminum cap marked as described in the official record of the 2001 resurvey.

With a steel fence post west of the corner.

Corner is located south of a fence line, 3-strand barbed-wire and metal posts, extending west and east where it terminates shortly at a wooden brace.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah

---

The Reestablishment of the Survey Executed by J. Bausman in 1870

---

From the corner of sections 1, 2, 35, and 36, Townships 24 and 25 South, Range 10 West, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, in a mound of stone, 2 feet diameter, 1 foot high, with aluminum cap, 3 1/4 inches diameter, marked SURVEY MARKER 1992 T24S S35/S36/S2/S1 T25S LS 6295 RESTORED BY MILLARD COUNTY. There is no remaining evidence of the 1870 wood post. This position is accepted as a careful and faithful reestablishment of the original corner position.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

**N. 89°58.3' W.**, between sections 2 and 35.

- 40.220** The 1/4 section corner of sections 2 and 35, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

ground, in a mound of stone, 2 1/2 feet diameter, 1 foot high, with aluminum cap, 3 1/4 inches diameter, marked SURVEY MARKER 1992 T24S R10W S35/S2 1/4 T25S LS 6295 RESTORED BY MILLARD COUNTY. There is no remaining evidence of the 1870 wood post. This position is accepted as a careful and faithful reestablishment of the original corner position.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

---

N. 89°59.9' W., beginning new measurement.

- 40.216 The corner of sections 2, 3, 34, and 35, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, in a mound of stone, 2 feet diameter, 1 foot high, with aluminum cap, 3 1/4 inches diameter, marked SURVEY MARKER 1992 T24S R10W S34/S35/S3/S2 T25S LS 6295 RESTORED BY MILLARD COUNTY. With a heavily weathered wood post, 8 inches diameter, firmly set, projecting 14 inches above the ground, alongside the corner. With a wood post, 5 inches diameter, 5 feet long, lying loose alongside the corner. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set loose, 5 inch diameter wood post north of the corner.

Corner is located in flat, level, open ground, with grasses.

---

N. 89°34.4' W., between sections 3 and 34.

- 40.104 The 1/4 section corner of sections 3 and 34, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 12 inches above the ground, in a mound of stone, 2 1/2 feet diameter, 1 foot high, with aluminum cap, 3 1/4 inches diameter, marked SURVEY MARKER 1992 T24S R10W S34/S3 1/4 T25S LS 6295 RESTORED BY MILLARD COUNTY. Found steel fence post to west. This position is accepted as a careful and faithful perpetuation of the original corner position.

Corner is located in flat, level, open ground, with grasses.

---

N. 89°52.6' W., beginning new measurement.

- 40.086 The corner of sections 3, 4, 33, and 34, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 11 inches above the ground, in a

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

scattered mound of stone, with aluminum cap, 3 1/4 inches diameter, marked SURVEY MARKER 1992 T24S R10W S33/S34/S4/S3 T25S LS 6295 RESTORED BY MILLARD COUNTY. This position is accepted as a careful and faithful perpetuation of the original corner position. Found a steel fence post south of the corner.

Rebuild mound of stone to 2 1/2 feet diameter, to cap.

Corner is located in flat, level, open ground, with blackbrush.

N. 89°55.0' W., between sections 4 and 33.

**33.585** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 12° E. and S. 12° W.

**40.424** Point for the 1/4 section corner of sections 4 and 33, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T24S R10W  
S33  
1/4 ———  
S4  
T25S  
2012

Set a steel fence post east of the corner.

Corner is located in fairly level ground, with brush.

**60.636** Point for the W 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T24S R10W  
S33  
W 1/16 ———  
S4  
T25S  
2012

Set a steel fence post north of the corner.

Corner is located in fairly level ground, with brush.

**80.848** The corner of sections 4, 5, 32, and 33, monumented with a wood post (1870 record: cedar post), heavily weathered, 4 inches square, firmly set, projecting 12 inches above the ground.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

At the corner (wood post)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T24S	R10W
S32	S33
S5	S4
T25S	
2012	

Bury wood post, 3 feet long, south of the corner.

Set a steel fence post southeast of the corner.

From corner, approximate intersection of old wooden post fence lines extending south and west, bears S. 43° W., 74 links distance.

Corner is located on fairly level ground, with brush.

N. 89°56.6' W., between sections 5 and 32.

- 40.084** The 1/4 section corner of sections 5 and 32, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with aluminum cap marked as described in the official record of the 2001 resurvey. Immediately alongside corner, a wood post, 2 inches diameter, projecting 14 inches above the ground, and a second wood post, 5 inches diameter, projecting 14 inches above the ground.

Set a steel fence post north of the corner.

Corner is located on flat, level ground, with blackbrush.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

The Reestablishment of the Survey Executed by J. Bausman in 1870.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

S. 89°33.7' W., between sections 24 and 25.

- 20.126** Point for the E 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W  
S24  
E 1/16  $\frac{\text{---}}{\text{S25}}$

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

- 40.252** The 1/4 section corner of sections 24 and 25, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 8 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 24/25 2008 LS 162522. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush and grasses.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

**S. 89°54.3' W.,** between sections 13 and 24.

- 40.151** Point for the 1/4 section corner of sections 13 and 24, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
S13  
1/4  $\frac{\text{---}}{\text{S24}}$

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

- 80.302** The corner of sections 13, 14, 23, and 24, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 12 inches

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 14/13/23/24 2008 LS 162522, with a wood post, heavily weathered, 4 x 4 inches square, firmly set, projecting 8 inches above the ground (1870 Record: wood post). This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

---

From the corner of sections 11, 12, 13, and 14, determined at the corner of fences, extending north and west. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T25S		R10W	
S11		S12	
S14		S13	
2012			

Set a steel fence post north of the corner.

From corner, a fence, consisting of only old wood posts lying on the ground, extends north.

From corner, a fence, with scattered remnants of old wood posts set in the ground remaining, projecting less than a foot above the ground, extends west.

Corner is located on fairly level, open ground, with grasses.

N. 0°00.5' W., between sections 11 and 12.

**40.081** Point for the 1/4 section corner of sections 11 and 12, at proportionate distance. There is no remaining evidence of the 1870 woodpost. Not monumented.

**80.162** Point for the corner of sections 1, 2, 11, and 12, at proportionate distance. There is no remaining evidence of the 1870 woodpost.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

S2	S1
S11	S12

2012

Set a steel fence post north of the corner.

From the corner, a rebar, 3/4 inch diameter, firmly set, flush with the ground, bears S. 61°54.0' W., 52.1 links distance. This unrecorded rebar was set using unknown procedures and was not utilized in the course of this resurvey.

Corner is located on flat, open ground, with grasses.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

N. 89°55.6' W., between sections 1 and 12.

- 40.270** Point for the 1/4 section corner of sections 1 and 12, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4	S1
	S12

2012

Set a steel fence post southeast of the corner.

Corner is located in fairly level ground, with grasses.

- 80.540** The corner of sections 1, 2, 11, and 12.

N. 0°02.8' E., between sections 1 and 2.

- 40.080** Point for the 1/4 section corner of sections 1 and 2, at proportionate distance. Found a wood post, 4 inches diameter, 3 ft. long lying loose on the ground. There is no method to determine the original location of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W

1/4

S2 | S1

2012

Set a steel fence post west of the corner.

From the corner, a steel fence post, projecting 2 1/2 feet above the ground, bears S. 23° E., 38.6 links distance.

Corner is located in fairly-level, open ground, with grasses.

- 80.441** The corner of sections 1, 2, 35, and 36, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 14, 15, 22, and 23, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 12 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 14/15/22/23 2008 LS 162522, with a rebar, 5/8 inch diameter, firmly set, flush with the ground, with a yellow plastic cap, 1 inch diameter, marked EDWARDS 162522, alongside, with a steel fence post, upside down, projecting 18 inches above the ground, alongside. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

From the corner, the corner of sections 13, 14, 23, and 24, bears N. 88°58.7' E., 80.826 chains distance.

Corner is located on flat, level, open ground, with grasses, approximately 30 links west of a 2-track road, bearing north and south.

N. 0°07.2' E., between sections 14 and 15.

- 40.436** Point for the 1/4 section corner of sections 14 and 15, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

1/4

S15		S14
-----	--	-----

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with low brush, approximately 30 links west of a dirt 2-track road bearing north and south.

- 80.872** Point for the corner of sections 10, 11, 14, and 15, at proportionate distance.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S10		S11
S15		S14

2012

Set a steel fence post north of the corner.

Corner is located on flat, level, open ground, with brush.

From the corner of sections 11, 12, 13, and 14.

**S. 88°49.6' W.**, between sections 11 and 14.

- 40.172** Point for the 1/4 section corner of sections 11 and 14, at proportionate distance. There is no remaining evidence of the 1870 wood post. Not monumented.

- 80.344** The corner of sections 10, 11, 14, and 15.

**N. 0°00.8' W.**, between sections 10 and 11.

- 40.436** Point for the 1/4 section corner of sections 10 and 11, at proportionate distance. Found a wood post, heavily weathered, 3 x 8 inches in diameter, 3 feet long, lying loose on the ground. There is no method to determine original location of post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W

1/4

S10	S11
-----	-----

2012

Set a steel fence post north of the corner.

Corner is located in fairly level, ground, with grasses.

- 80.872** Point for the corner of sections 2, 3, 10, and 11, at proportionate distance. There is no remaining evidence of the 1870 wood post. Found loose unmarked iron pipe nearby.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S3	S2
S10	S11

2012

Set a steel fence post north of the corner.

Corner is located on flat, level, open ground, with grasses.

From the corner of sections 1, 2, 11, and 12.

**S. 89°20.0' W.**, between sections 2 and 11.

- 40.162** Point for the 1/4 section corner of sections 2 and 11, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4	S2
	S11

2012

Set a steel fence post west of the corner.

Corner is located in fairly level ground, with grasses.

- 80.324** The corner of sections 2, 3, 10, and 11.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

N. 0°02.9' W., between sections 2 and 3.

- 40.436 Point for the 1/4 section corner of sections 2 and 3, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4

S3 | S2

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with brush.

- 81.398 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 1°08.5' W., between sections 33 and 34.

- 40.282 The 1/4 section corner of sections 33 and 34, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 17 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 33/34 2008 LS 162522. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

---

N. 1°08.7' W., begin new measurement.

- 40.279 The corner of sections 27, 28, 33, and 34, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 17 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 28/27/33/34 2008 LS 162522; remnants of a wood post scattered around the corner. This position is accepted as a careful and faithful perpetuation of the original corner position.

---

Set a steel fence post north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

From the 1/4 section corner of sections 27 and 34, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 18 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 27/34 2008 LS 162522. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

N. 89°28.8' W., between sections 27 and 34.

20.289 Point for the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
	S27
W 1/16	-----
	S34

2012

Set a steel fence post north of the corner.

Corner is located in fairly level, open ground, with blackbrush.

40.578 The corner of sections 27, 28, 33, and 34.

---

N. 0°08.2' W., between sections 27 and 28.

40.806 The 1/4 section corner of sections 27 and 28, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 13 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 28/27 2008 LS 162522; remnants of a wood post scattered around the corner. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

---

From the corner of sections 15, 16, 21, and 22, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 11

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 16/15/22/21 2008 LS 162522. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

From the corner, a steel fence post, projecting 2 1/2 feet above the ground, bears N. 25° E., approximately 3 chains distance.

Corner is located in flat, level, open ground, with blackbrush and grasses.

N. 0°47.5' E., between sections 15 and 16.

- 40.414** Point for the 1/4 section corner of sections 15 and 16, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, to bedrock, magnet at base, in a mound of stone, 3 feet diameter, to cap, with aluminum cap marked

T25S R10W

1/4

S16 | S15

2012

Set a steel fence post north of the corner.

Corner is located in gently rolling, open ground, with low brush.

- 80.828** Point for the corner of sections 9, 10, 15, and 16, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S9 | S10

S16 | S15

2012

Set a steel fence post north of the corner.

From the corner, a wooden post, 11 inches diameter, firmly set, projecting 2 feet above the ground, bears S. 33°33' E., 3.84 chains distance. Other old homestead debris nearby.

Corner is located on flat, level, open ground, with low brush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

From the corner of sections 10, 11, 14, and 15.

**N. 89°20.5' W.**, between sections 10 and 15.

- 40.176** Point for the 1/4 section corner of sections 10 and 15, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
	S10
1/4	<u>        </u>
	S15

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with low brush.

- 60.264** Point for the W 1/16 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
	S10
W 1/16	<u>        </u>
	S15

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with low brush.

- 80.352** The corner of sections 9, 10, 15, and 16.

---

**N. 0°03.2' W.**, between sections 9 and 10.

- 40.410** Point for the 1/4 section corner of sections 9 and 10, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

1/4

S9	S10
----	-----

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses and scattered brush.

**60.615** Point for the N 1/16 section corner of sections 9 and 10. Not monumented.

**80.820** Point for the corner of sections 3, 4, 9, and 10, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S4	S3
S9	S10

2012

Set a steel fence post north of the corner.

Corner is located on flat, level, open ground, with grasses and low brush.

---

From the corner of sections 2, 3, 10, and 11.

**N. 89°22.7' W.,** between sections 3 and 10.

**40.197** Point for the 1/4 section corner of sections 3 and 10, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4	S3
	S10

2012

---

Set a steel fence post north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

Corner is located in flat, level, open ground, with low brush.

80.394 The corner of sections 3, 4, 9, and 10.

---

N. 0°04.8' E., between sections 3 and 4.

40.410 Point for the 1/4 section corner of sections 3 and 4, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4

S4 | S3

2012

Set a steel fence post south of the corner.

Corner is located in flat, level, open ground, with grasses.

80.911 The corner of sections 3, 4, 33, and 34, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 27, 28, 33, and 34.

N. 89°52.7' W., between sections 28 and 33.

40.329 Point for the 1/4 section corner of sections 28 and 33, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4  $\frac{S28}{S33}$

2012

Set a steel fence post north of the corner.

From the corner, an aluminum rod, 1 inch diameter, firmly set, projecting 18 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 1/4 28/33 2008 LS 162522, set by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, bears S. 32°26' E., 7 links distance. This monument was set using



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

unknown procedures and was not utilized in the course of this resurvey.

Corner is located in flat, level, open ground, with scattered blackbrush.

**60.493** Point for the W 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

	T25S	R10W
		S28
W 1/16		<u>          </u>
		S33

2012

Set a steel fence post north of the corner.

Corner is located approximately 30 links west of an old highway grade extending north and south; in flat, level, open ground, with blackbrush.

**65.487** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 5° E. and S. 5° W.

**80.657** The corner of sections 28, 29, 32, and 33, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 16 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 29/28/32/33 2008 LS 162522, with a heavily weathered wooden post, 4" x 4", firmly set, projecting 2 feet above the ground to the west. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

From the corner, two wood posts set together, 4 x 4 inches square, projecting 3 feet above the ground, bear N. 58°40' W., 24.2 links distance.

N. 0°13.0' E., between sections 28 and 29.

**40.284** The 1/4 section corner of sections 28 and 29, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 17 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 29/28 2008 LS 162522, with a wooden post (1870 Record: cedar post), heavily

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

weathered, 4 inches diameter, firmly set, projecting 2 feet above the ground alongside aluminum rod. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

---

N. 1°04.2' W., beginning new measurement.

- 40.210** The corner of sections 20, 21, 28, and 29, monumented by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 13 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 20/21/29/28 2008 LS 162522. This monument is located at the corner of old cedar post fences, with 4-strand rusty barbed wire, extending south and west. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

Corner is located on fairly level ground, with brush and tamarisk trees.

---

From the 1/4 section corner of sections 21 and 28, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 12 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 21/28 1/4 2008 LS 162522. Found remnants of wood posts, various diameters and lengths, with no visible markings, lying loose on the ground nearby. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

S. 89°35.9' W., between sections 21 and 28.

- 17.608** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

- 20.331** Point for the W 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W  
S21  
W 1/16           
S28

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered blackbrush.

40.662 The corner of sections 20, 21, 28, and 29.

---

N. 0°08.3' E., between sections 20 and 21.

40.303 Point for the 1/4 section corner of sections 20 and 21, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
1/4  
S20 | S21  
2012

Set a steel fencepost north of the corner.

From the corner, an aluminum rod, 1 inch diameter, firmly set, projecting 14 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 20/21 1/4 2008 LS 162522, set by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, bears S. 76°13' W., 42.5 links distance. This monument was set using unknown procedures and was not utilized in the course of this resurvey.

Corner is located in an area of low sand dunes, with blackbrush.

80.606 Point for the corner of sections 16, 17, 20, and 21, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W

S17	S16
S20	S21

2012

Set a steel fence post north of the corner.

From the corner, an aluminum rod, 1 inch diameter, was found nearby lying loose on the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 17/16/20/21 2008 LS 162522, set by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008. An unknown method was used to set this monument, and it was not utilized in this resurvey. As there is no remaining evidence as to the original location of this monument, it is removed.

Corner is located in an area of windblown sand and low sand dunes.

---

From the 1/4 section corner of sections 16 and 21, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 17 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 16/21 1/4 2008 LS 162522. Found a remnant of a wood post, 4 x 4 inches diameter, 3 feet long, with no visible markings, lying loose on the ground nearby. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

N. 89°03.6' W., between sections 16 and 21.

11.316 Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

39.948 The corner of sections 16, 17, 20, and 21.

---

N. 0°45.0' E., between sections 16 and 17.

40.306 Point for the 1/4 section corner of sections 16 and 17, at proportionate distance. There is no remaining evidence of the 1870 wood post. Not monumented.

---

80.612 Point for the corner of sections 8, 9, 16, and 17, at proportionate distance. There is no remaining evidence of the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.  
CHAINS

1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
S8	S9
S17	S16
2012	

Set a steel fence post north of the corner.

Corner is located in an area of low sand dunes and shifting sand, with no vegetation.

From the corner of sections 9, 10, 15, and 16.

**N. 89°22.3' W.**, between sections 9 and 16.

- 40.282** The 1/4 section corner of sections 9 and 16, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
1/4	S9
	S16
2012	

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

- 47.270** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

- 80.564** The corner of sections 8, 9, 16, and 17.

**N. 0°07.2' E.**, between sections 8 and 9.

- 40.303** Point for the 1/4 section corner of sections 8 and 9, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

1/4

S8	S9
----	----

2012

Set a steel fence post north of the corner.

Corner is located in an area of low sand dunes and drifting sand,  
with no vegetation.

**60.454** The point for the N 1/16 section corner of sections 8 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23  
inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

N 1/16

S8	S9
----	----

2012

Set a steel fence post alongside the corner.

Corner is located on level ground with scattered sagebrush.

**80.605** Point for the corner of sections 4, 5, 8, and 9, at proportionate  
distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25  
inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S5	S4
S8	S9

2012

Set a steel fence post north of the corner.

Corner is located in sand dunes, east of a broad wash.

From the corner of sections 3, 4, 9, and 10.

**N. 89°31.4' W.**, between sections 4 and 9.

**20.075** Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26  
inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W  
E 1/16  $\frac{S4}{S9}$

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

- 40.150** Point for the 1/4 section corner of sections 4 and 9, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set a 60d nail, 6 inches below the grade of an unimproved gravel road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 29 inches in the ground, with magnet at base, for a reference monument, bears S. 16°48.1' W., 45.7 links distance, with aluminum cap marked RM T25S R10W S9 30.2 FT. TO COR. 2012 and an arrow pointing to the corner. Set a steel fence post east of aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 29 inches in the ground, with magnet at base, for a reference monument, bears N. 65°26.6' W., 29.7 links distance, with aluminum cap marked RM T25S R10W S4 19.6 FT. TO COR. 2012 and an arrow pointing to the corner. Set a steel fence post east of aluminum post.

From the corner, the centerline of the Union Pacific Railroad tracks, bearing northerly and southerly, bears East, 70.3 links distance.

Corner is located in flat, level, open ground, with scattered blackbrush.

- 41.531** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

- 80.300** The corner of sections 4, 5, 8, and 9.

---

N. 0°19.4' W., between sections 4 and 5.

- 40.306** Point for the 1/4 section corner of sections 4 and 5, determined latitudinally by an old cedar post fence (extends west). There is no remaining evidence of the 1870 wood post.

~~Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked~~

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

1/4

S5 | S4

2012

Set a steel fencepost east of the corner.

From corner, a rectangular wooden post, 8 x 6 inches, firmly set, projecting 4 ft. above ground, bears N. 76°24' W., 0.831 chain distance.

Corner is located in an area of low sand dunes and drifting sand, adjacent to a broad, sandy wash.

- 80.362** The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, monumented with an aluminum cap, 3 inches diameter, firmly set flush in cement, marked as described in the official record of the 2011-2012 resurvey, with a steel fence post west of the corner.

From the corner, abandoned fences, only scattered wood posts and segments of barbed-wire remaining, extend easterly, westerly, and southerly.

**N. 0°09.4' E.**, between sections 31 and 32.

- 20.190** Point for the S 1/16 section corner of sections 31 and 32. Not monumented.

- 40.380** The 1/4 section corner of sections 31 and 32, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on an unrecorded survey described as "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM", dated September 20, 2011, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 13 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 31/32 1/4 2008 LS 162522. This position is accepted as a careful and faithful reestablishment of the original corner position.

From the corner, the extrapolated intersection point of several abandoned fences, only scattered wood posts remaining, extending northerly, easterly, and westerly, bears North, 9 links distance.

---

**N. 0°09.0' E.**, beginning new measurement.

- 20.190** Point for the N 1/16 section corner of sections 31 and 32.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

N 1/16

S31 | S32

2012

Set a steel fence post north of the corner.

Corner is located in gently-rolling ground, with tamarisk brush.

- 40.380** The corner of sections 29, 30, 31, and 32, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on an unrecorded survey described as "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM", dated September 20, 2011, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 11 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 30/29/31/32 2008 LS 162522. This position is accepted as a careful and faithful reestablishment of the original corner position.

From the corner, an abandoned fence, only scattered wood posts remaining, extending northerly and southerly, bears East, 29 links distance.

---

From the corner of sections 28, 29, 32, and 33.

N. 89°40.4' W., between sections 29 and 32.

- 40.379** The 1/4 section corner of sections 29 and 32, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on an unrecorded survey described as "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM", dated September 20, 2011, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 8 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 29/32 1/4 2008 LS 162522, with the remnant of a wood post, 4 inches diameter, 16 inches long, lying loose on the ground alongside. This position is accepted as a careful and faithful reestablishment of the original corner position.

Set a steel fence post north of the corner.

---

N. 89°40.8' W., beginning new measurement.

- 40.379** The corner of sections 29, 30, 31, and 32.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S. 89°52.4' W., between sections 30 and 31.

- 40.388 Point for the 1/4 section corner of sections 30 and 31, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
	S30
1/4	<u>          </u>
	S31

2012

Set a steel fence post north of the corner.

From the corner, an aluminum rod, 1 inch diameter, firmly set, projecting 14 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 1/4 30/31 2008 LS 162522, set by James D. Edwards, Utah PLS 162522, as shown on an unrecorded survey described as "DEPENDENT RE-SURVEY SECTIONS 32 & 33, T25S, R10W, SLM AND SECTIONS 26, 35, & 36, T25S, R11W, SLM", dated September 20, 2011, bears S. 89°44' W., 12.2 links distance. This monument was set using unknown procedures and was not utilized in the course of this resurvey.

From the corner, a fence line, wood post and 4-strand barbed-wire, extending northerly and southerly, bears East, 60 links distance.

Corner is located in flat, level, open ground, with blackbrush.

- 60.582 Point for the W 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
	S30
W 1/16	<u>          </u>
	S31

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered blackbrush.

- 81.019 The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 29, 30, 31, and 32.

N. 0°00.6' E., between sections 29 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

**20.055** Point for the S 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S 1/16

S30 | S29

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with sparse vegetation.

**40.110** Point for the 1/4 section corner of sections 29 and 30, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4

S30 | S29

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered tamarisk trees.

**60.165** Point for the N 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

N 1/16

S30 | S29

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with sparse vegetation.

~~**80.220** Point for the corner of sections 19, 20, 29, and 30, determined latitudinally by an old fence line, wood post and 4-strand~~

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

barbed-wire, extends easterly and westerly, and longitudinally by proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
S19	S20
S30	S29

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered brush.

From the corner of sections 20, 21, 28, and 29.

N. 89°51.6' W., between sections 20 and 29.

- 40.064** Point for the 1/4 section corner of sections 20 and 29, determined latitudinally by an old fence, wood post and 4-strand barbed-wire, extending north, east, and west and longitudinally by proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 23 inches in the ground, magnet at base, with aluminum cap marked

T25S	R10W
1/4	S20
	S29

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered blackbrush.

N. 89°52.2' W., beginning new measurement.

- 40.064** The corner of sections 19, 20, 29, and 30.

N. 89°52.7' W., between sections 19 and 30.

- 39.910** The 1/4 section corner of sections 19 and 30, determined at the corner of old fences, wood posts and 4-strand barbed-wire, extending north, south, and east. This position is harmoniously

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

related to existing corners and is accepted as the best available evidence of the original corner. There is no remaining evidence of the 1870 wood post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

	S19
1/4	<hr/>
	S30

2012

Corner is located in flat, level, open ground, with blackbrush.

---

N. 89°28.3' W., beginning new measurement.

**20.137** Point for the W 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

	S19
W 1/16	<hr/>
	S30

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**40.536** The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 19, 20, 29, and 30.

N. 0°00.4' E., between sections 19 and 20.

**40.514** Point for the 1/4 section corner of sections 19 and 20, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.  
CHAINS

T25S R10W

1/4

S19	S20
-----	-----

2012

Set a steel fence post north of the corner.

Corner is located in flat, level ground, with blackbrush.

- 81.028** Point for the corner of sections 17, 18, 19, and 20, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

S18	S17
S19	S20

2012

Set a steel fence post north of the corner.

Corner is located in flat, level ground, with scattered tamarisk trees.

From the corner of sections 16, 17, 20, and 21.

**N. 89°33.8' W.**, between sections 17 and 20.

- 20.075** Point for the E 1/16 section corner of sections 17 and 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

	S17
E 1/16	S20

2012

Set a steel fence post north of the corner.

Corner is located in flat, level ground, with scattered blackbrush.

- 40.150** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance. There is no remaining evidence of the 1870 wood post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4  $\frac{S17}{S20}$

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with sparse vegetation.

**80.299** The corner of sections 17, 18, 19, and 20.

---

**N. 89°47.6' W.**, between sections 18 and 19.

**40.030** Point for the 1/4 section corner of sections 18 and 19, determined longitudinally by an old fence, wood post and 3-strand barbed-wire, extending north and south. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4  $\frac{S18}{S19}$

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**59.869** Point for the W 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

W 1/16  $\frac{S18}{S19}$

2012

Set a steel fence post north of the corner.

Corner is located in brushy terrain.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 79.866** The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 17, 18, 19, and 20.

**N. 0°26.6' E.**, between sections 17 and 18.

- 40.516** Point for the 1/4 section corner of sections 17 and 18, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

1/4

S18 | S17

2012

Set a steel fencepost north of the corner.

Corner is located in flat, level ground, with blackbrush.

- 81.032** The corner of sections 7, 8, 17, and 18, monumented by James D. Edwards, Utah PLS 162522, monumented with an unrecorded aluminum rod, 1 inch diameter, firmly set, projecting 13 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 7/8/18/17 2006 LS 162522, at the corner of old cedar post fences, extending northerly and easterly. There is no remaining evidence of the 1870 wood post. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

Corner is located on fairly level, open ground.

---

From the corner of sections 8, 9, 16, and 17.

**N. 89°15.9' W.**, between sections 8 and 17.

- 40.358** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance. There is no remaining evidence of the 1870 wood post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

$$\begin{array}{r} 1/4 \quad \frac{S8}{S17} \end{array}$$

2012

Set a steel fence post north of the corner.

From the corner, the extrapolated intersection point of several abandoned fencelines, only scattered wood posts and remnants of barbed wire remaining, extending northerly, southerly, and westerly, bears N. 7° W., 70 links distance

Corner is located in fairly level ground, with grasses.

**80.716** The corner of sections 7, 8, 17, and 18.

---

**S. 89°50.6' W.**, between sections 7 and 18.

**40.238** Point for the 1/4 section corner of sections 7 and 18, determined longitudinally by an old cedar post fence. There is no remaining original evidence from the 1870 survey.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

$$\begin{array}{r} 1/4 \quad \frac{S7}{S18} \end{array}$$

2012

Set a steel fence post north of the corner.

Corner is located in fairly level ground, with brush.

**60.256** Point for the W 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

$$\begin{array}{r} W \ 1/16 \quad \frac{S7}{S18} \end{array}$$

2012

Set a steel fence post north of the corner.

---

From the corner, a wood post, heavily weathered, 5 inches

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

diameter, firmly set, projecting 8 inches above the ground, bears N.  $1^{\circ}$  E., 38.6 links distance.

Corner is located in fairly level ground, with brush.

- 80.405 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 7, 8, 17, and 18.

N.  $0^{\circ}12.1'$  E., between sections 7 and 8.

- 40.168 Point for the  $1/4$  section corner of sections 7 and 8, determined at the corner of old cedar post fences, only wood posts and remnants of barbed-wire remaining, extending northerly, southerly, and easterly. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. There is no remaining original evidence of the 1870 wood post corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

$1/4$

S7 | S8

2012

From the corner, an unrecorded steel spike, 5/16 inch diameter, firmly set, projecting 1 inch above the ground, with yellow plastic cap, 1 inch diameter, marked EDWARDS 162522, set by James D. Edwards, Utah PLS 162522, bears S.  $41^{\circ}00'$  W., 12.2 links distance; with steel fence posts to the north, south, and east. This monument was set using unknown procedures and was not utilized in the course of this resurvey.

Corner is located in flat, level, open ground, with blackbrush.

---

N.  $0^{\circ}15.0'$  E., beginning new measurement.

- 39.252 The corner of sections 5, 6, 7, and 8, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2001 resurvey, with a steel fence post east of the corner, and a round wood post, 5 inches diameter, 4 feet long, with one end cut and previously buried 16 inches in the ground, with nails in it, is lying loose alongside the corner, and the remnant of a wood post, 3 inches diameter, firmly set, projecting 12 inches above the ground, with barbed-wire wrapped around it, is north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner, abandoned fences, only scattered remnants of wood posts remaining, extend southerly and easterly.

Corner is located on flat, level ground, with blackbrush.

---

From the corner of sections 4, 5, 8, and 9.

**S. 89°34.8' W.**, between sections 5 and 8.

- 40.417** Point for the 1/4 section corner of sections 5 and 8, determined at the corner of abandoned fences, only wood posts and remnants of barbed-wire remaining, extending southerly, and westerly. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. There is no remaining evidence of the 1870 wood post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

	S5
1/4	<hr/>
	S8

2012

Set a steel fence post north of the corner.

Remains of a buried wood post found, 2 feet below the ground, when setting the aluminum post.

Corner is located in gently rolling ground, with blackbrush.

---

**N. 89°47.6' W.**, beginning new measurement.

- 40.134** The corner of sections 5, 6, 7, and 8.

---

Subdivision of Section 1,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 1 and 12.

**N. 0°00.9' E.**, on the N-S centerline of section 1.

- 40.167** Point for the center 1/4 section corner of section 1, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

SUBDIVISION OF SECTION 1,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W  
C 1/4 S1  
2012

Set a steel fence post northeast of the corner.

Corner is located in fairly level ground, with grasses.

- 80.474** The 1/4 section corner of sections 1 and 36, on the north boundary of the township, monumented by Kary B. Monroe, as shown on "MILLARD COUNTY SECTION CORNER SURVEY" dated December 10, 1992, on file at the Millard County Recorder's Office, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 10 inches above the ground, in a mound of stone, 2 feet diameter, to cap, with aluminum cap, 3 1/4 inches diameter, marked SURVEY MARKER 1992 T24S R10W 1/4 S36/S1 T25S LS 6295 RESTORED BY MILLARD COUNTY. There is no remaining evidence of the 1870 wood post. This position is accepted as a careful and faithful determination of the position of the original corner position.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

From the 1/4 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

**S. 89°57.1' W.**, on the E-W centerline of section 1.

- 40.243** The center 1/4 section corner of section 1.

- 80.486** The 1/4 section corner of sections 1 and 2.

Subdivision of Section 2,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 2 and 11.

**N. 0°00.2' W.**, on the N-S centerline of section 2.

- 40.258** Point for the center 1/4 section corner of section 2, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

SUBDIVISION OF SECTION 2,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W

C 1/4 S2

2012

Set a steel fence post west of the corner.

Corner is located in fairly level ground, with grasses.

- 80.929** The 1/4 section corner of sections 2 and 35, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 1 and 2.

**S. 89°35.2' W.**, on the E-W centerline of section 2.

- 40.190** The center 1/4 section corner of section 2.

- 80.378** The 1/4 section corner of sections 2 and 3.

---

Subdivision of Section 3,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 3 and 10.

**N. 0°00.5' E.**, on the N-S centerline of section 3.

- 40.423** Point for the center 1/4 section corner of section 3, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S3

2012

Set a steel fence post south of the corner.

Corner is located in flat, level, open ground, with grasses and scattered brush.

- 81.260** The 1/4 section corner of sections 3 and 34, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 2 and 3.

**N. 89°23.8' W.**, on the E-W centerline of section 3.

- 
- 40.152** The center 1/4 section corner of section 3.

SUBDIVISION OF SECTION 3,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

80.294 The 1/4 section corner of sections 3 and 4.

---

Subdivision of Section 4,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 4 and 9.

N. 0°07.2' W., on the N-S centerline of section 4.

40.357 Point for the center 1/4 section corner of section 4, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S4

2012

Set a steel fence post west of the corner.

Corner is located in gently rolling ground, with desert vegetation.

80.635 The 1/4 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 3 and 4.

N. 89°35.9' W., on the E-W centerline of section 4.

38.717 Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

40.288 The center 1/4 section corner of section 4.

60.432 Point for the center W 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

W 1/16  
C  $\frac{\quad}{\quad}$  C  
S4

2012

Set a steel fence post west of the corner.

Corner is located in gently rolling ground, with desert vegetation.

---

SUBDIVISION OF SECTION 4,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

**80.576** The 1/4 section corner of sections 4 and 5.

---

From the center W 1/16 section corner of section 4.

**N. 0°13.3' W.**, on the N-S centerline of the NW 1/4 of section 4.

**40.167** The W 1/16 section corner of sections 4 and 33, on the north boundary of the township, hereinbefore described.

---

Subdivision of Section 8,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 8 and 17.

**N. 0°04.3' E.**, on the N-S centerline of section 8.

**40.236** Point for the center 1/4 section corner of section 8, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S8

2012

Set a steel fence post east of the corner.

From this corner, the corner of an old wood post fence bears N. 27° W., 12.9 links distance, only wood posts and remnants of barbed-wire remain, extending north, south, and east.

**60.014** Point for the center N 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C  
N 1/16 | S8  
C

2012

Set a steel fence post north of the corner.

Corner is located in an old fence, wood posts and remnants of barbed-wire, extending north and south.

**79.792** The 1/4 section corner of sections 5 and 8.

---

SUBDIVISION OF SECTION 8,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the 1/4 section corner of sections 8 and 9.

**N. 89°21.7' W.**, on the E-W centerline of section 8.

**40.387** The center 1/4 section corner of section 8.

**80.649** The 1/4 section corner of sections 7 and 8.

From the N 1/16 section corner of sections 8 and 9.

**N. 89°53.4' W.**, on the E-W centerline of the NE 1/4 of section 8.

**40.400** The center N 1/16 section corner of section 8.

Subdivision of Section 9,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 9 and 16.

**N. 0°02.0' E.**, on the N-S centerline of section 9.

**40.357** Point for the center 1/4 section corner of section 9, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S9  
2012

Set a steel fence post north of the corner.

Corner is located east of the easterly right-of-way fence of the Union Pacific Railroad tracks; on flat, level, open ground, with grasses.

**60.535** Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C  
N 1/16 | S9  
C  
2012

~~Set a steel fence post north of the corner.~~



SUBDIVISION OF SECTION 9,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From corner, center line of railroad tracks bears West, 72 links distance.

Corner is located in flat, level ground.

**80.713** The 1/4 section corner of sections 4 and 9.

---

From the 1/4 section corner of sections 9 and 10.

**N. 89°26.8' W.**, on the E-W centerline of section 9.

**20.108** Point for the center E 1/16 section corner of section 9. Not monumented.

**40.216** The center 1/4 section corner of section 9.

**44.396** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

**80.432** The 1/4 section corner of sections 8 and 9.

---

From the point for the center E 1/16 section corner of section 9.

**N. 0°00.6' W.**, on the N-S centerline of the NE 1/4 of section 9.

**20.192** Point for the NE 1/16 section corner of section 9, at intersection with the E-W centerline of the NE 1/4 of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

NE 1/16 S9

2012

Set a steel fence post north of the corner.

From the corner, the extrapolated intersection point of several abandoned fences (only scattered wood posts and barbed-wire remnants remaining), extending southerly and westerly, bears N. 40° W., 103 links distance.

Corner is located in flat, level, open ground, with grasses.

**40.384** The E 1/16 section corner of sections 4 and 9.

---

From the point for the N 1/16 section corner of sections 9 and 10.

**N. 89°29.1' W.**, on the E-W centerline of the NE 1/4 of section 9.

**20.092** The NE 1/16 section corner of section 9.

---

**40.184** The center N 1/16 section corner of section 9.

SUBDIVISION OF SECTION 10,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Subdivision of Section 10,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 10 and 15.

**N. 0°02.0' W.**, on the N-S centerline of section 10.

- 40.423** Point for the center 1/4 section corner of section 10, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S10  
2012

Set a steel fence post north of the corner.

Corner is located in fairly level, open ground, with grasses.

- 80.846** The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

**N. 89°21.6' W.**, on the E-W centerline of section 10.

- 40.186** The center 1/4 section corner of section 10.

- 60.279** Point for the center W 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C  $\frac{W 1/16}{S10}$  C  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses.

- 80.372** The 1/4 section corner of sections 9 and 10.

From the W 1/16 of sections 10 and 15.

**N. 0°02.6' W.**, on the N-S centerline of the SW 1/4 of section 10.

SUBDIVISION OF SECTION 10,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

**40.417** The center W 1/16 section corner of section 10.

---

Subdivision of Section 15,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 15 and 22, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 14 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 15/22 1/4 2008 LS 162522, with a remnant of a wood post, 4 x 4 inches diameter, 11 inches long, lying loose alongside. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**N. 0°27.1' E.**, on the N-S centerline of section 15.

**40.421** Point for the center 1/4 section corner of section 15, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S15  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with low brush.

**80.846** The 1/4 section corner of sections 10 and 15.

---

From the 1/4 section corner of sections 14 and 15.

**N. 89°19.6' W.**, on the E-W centerline of section 15.

**40.415** The center 1/4 section corner of section 15.

**80.835** The 1/4 section corner of sections 15 and 16.

---

Subdivision of Section 18,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 18 and 19.

**N. 0°17.5' E.**, on the N-S centerline of section 18.

SUBDIVISION OF SECTION 18,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

- 40.388** Point for the center 1/4 section corner of section 18, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S18

2012

Set a steel fence post north of the corner.

From the corner, a wood post, heavily weathered, 5 inches diameter, firmly set, projecting 12 inches above the ground, bears S. 39° E., 17.1 links distance.

Corner is located in fairly level ground, with brush.

- 80.776** The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18.

**N. 89°58.5' W.**, on the E-W centerline of section 18.

- 40.133** The center 1/4 section corner of section 18.

- 60.059** Point for the center W 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

W 1/16  
C  $\frac{\quad}{S18}$  C

2012

Set a steel fence post north of the corner.

Corner is located north of an earthen berm, with brush and tamarisk trees.

- 80.135** The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

From the W 1/16 section corner of sections 18 and 19.

**N. 0°09.9' E.**, on the N-S centerline of the SW 1/4 of section 18.

- 40.325** The center W 1/16 section corner of section 18.

SUBDIVISION OF SECTION 18,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

**N. 0°09.4' E.**, on the N-S centerline of the NW 1/4 of section 18.

**40.325** The W 1/16 section corner of sections 7 and 18.

Subdivision of Section 19,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 19 and 30.

**N. 0°05.0' W.**, on the N-S centerline of section 19.

**40.616** Point for the center 1/4 section corner of section 19, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S19  
2012

Set a steel fence post west of the corner.

Corner located in an old fence, with wood posts and 3-strand barbed-wire, extending north and south.

Corner is located in flat, level, and open ground, with blackbrush.

**60.852** Point for the center N 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C  
N 1/16 | S19  
C  
2012

Set a steel fence post west of the corner.

Corner lies in an old fence, with wood posts and 3-strand barbed-wire, extending north and south.

Corner is located in flat, level, open ground, with blackbrush and mormon tea.

**81.088** The 1/4 section corner of sections 18 and 19.

SUBDIVISION OF SECTION 19,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

From the 1/4 section corner of sections 19 and 20.

**N. 89°44.0' W.**, on the E-W centerline of section 19.

**39.970** The center 1/4 section corner of section 19.

**59.953** Point for the center W 1/16 section corner of section 19. Not monumented.

**80.156** The 1/4 section corner of sections 19 and 24, on the west boundary of the township, hereinbefore described.

From the point for the center W 1/16 section corner of section 19.

**N. 0°07.1' E.**, on the N-S centerline of the NW 1/4 of section 19.

**20.226** Point for the NW 1/16 section corner of section 19, at intersection with the E-W centerline of the NW 1/4 of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
NW 1/16 S19  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**40.452** The W 1/16 section corner of sections 18 and 19.

From the center N 1/16 section corner of section 19.

**N. 89°45.8' W.**, on the E-W centerline of the NW 1/4 of section 19.

**19.911** The NW 1/16 section corner of section 19.

**40.011** The point for the N 1/16 section corner of sections 19 and 24, on the west boundary of the township.

Subdivision of Section 20,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 20 and 29.

**N. 0°04.3' E.**, on the N-S centerline of section 20.

**40.405** Point for the center 1/4 section corner of section 20, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24

SUBDIVISION OF SECTION 20,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S20

2012

Set a steel fence post north of the corner.

From the corner, the extrapolated intersection point of two abandoned fence lines, only scattered wood posts remaining, extending southerly and easterly, bears easterly, 59 links distance.

Corner is located in flat, level, open ground, with sparse vegetation.

**80.814** The 1/4 section corner of sections 17 and 20.

---

From the 1/4 section corner of sections 20 and 21.

**N. 89°42.9' W.**, on the E-W centerline of section 20.

**20.053** Point for the center E 1/16 section corner of section 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

E 1/16  
C  $\frac{\quad}{\quad}$  C  
S 20

2012

Set a steel fence post north of the corner.

Corner is located on flat, fairly-level ground, in scattered blackbrush.

**40.106** The center 1/4 section corner of section 20.

**80.213** The 1/4 section corner of sections 19 and 20.

---

From the center E 1/16 section corner of section 20.

**N. 0°06.3' E.**, on the N-S centerline of the NE 1/4 of section 20.

**40.356** The E 1/16 section corner of sections 17 and 20.

SUBDIVISION OF SECTION 21,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

---

Subdivision of Section 21,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 21 and 28.

**N. 0°22.3' W.**, on the N-S centerline of section 21.

- 39.886** Point for the center 1/4 section corner of section 21, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S21

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

- 79.667** The 1/4 section corner of sections 16 and 21.
- 

From the 1/4 section corner of sections 21 and 22, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 16 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 21/22 1/4 2008 LS 162522. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**N. 89°48.6' W.**, on the E-W centerline of section 21.

- 40.616** The center 1/4 section corner of section 21.

- 55.105** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

- 60.767** Point for the center W 1/16 section corner of section 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

---



SUBDIVISION OF SECTION 21,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

T25S R10W

$$\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S21} \end{array}$$

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**80.918** The 1/4 section corner of sections 20 and 21.

---

From the W 1/16 section corner of sections 21 and 28.

**N. 0°06.9' W.**, on the N-S centerline of the SW 1/4 of section 21.

**40.094** The center W 1/16 section corner of section 21.

---

Subdivision of Section 24,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 24 and 25.

**N. 0°05.5' E.**, on the N-S centerline of section 24.

**40.424** Point for the center 1/4 section corner of section 24, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S24

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**80.679** The 1/4 section corner of sections 13 and 24.

---

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

**S. 89°51.3' W.**, on the E-W centerline of section 24.

**20.101** Point for the center E 1/16 section corner of section 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

SUBDIVISION OF SECTION 24,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W

$$\begin{array}{c} \text{E } 1/16 \\ \text{C } \frac{\quad}{\quad} \text{C} \\ \text{S24} \\ 2012 \end{array}$$

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**40.202** The center 1/4 section corner of section 24.

**80.249** The 1/4 section corner of sections 23 and 24, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 13 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 23/24 1/4 2008 LS 162522. Found a remnant of a wood post, heavily weathered, 2 x 4 inches diameter, firmly set, projecting 13 inches above the ground, with no visible markings, alongside. This position is accepted as a careful and faithful perpetuation of the original corner position.

Set a steel fence post north of the corner.

From the E 1/16 section corner of sections 24 and 25.

**N. 0°03.6' E.**, on the N-S centerline of the SE 1/4 of section 24.

**40.322** The center E 1/16 section corner of section 24.

Subdivision of Section 27,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 27 and 34.

**N. 0°03.1' W.**, on the N-S centerline of section 27.

**40.389** Point for the center 1/4 section corner of section 27, at intersection with the E-W centerline.

Set a 60d nail, 6 inches below the grade of an improved gravel road, 20 feet wide, extending east and west.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 25 inches in the ground, with magnet at base, for a reference monument, bears S. 45°29.6' E., 31.7 links

SUBDIVISION OF SECTION 27,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

distance, with aluminum cap marked RM T25S R10W S27 20.9 FT. TO COR. 2012 and an arrow pointing to the corner. Set a steel fence post north of aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, with magnet at base, for a reference monument, bears S. 38°51.0' W., 27.9 links distance, with aluminum cap marked RM T25S R10W S27 18.4 FT. TO COR. 2012 and an arrow pointing to the corner. Set a steel fence post north of aluminum post.

- 80.587** The 1/4 section corner of sections 22 and 27, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 14 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 1/4 22/27 2008 LS 162522. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

From the 1/4 section corner of sections 26 and 27, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 12 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 27/26 2008 LS 162522. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

**N. 88°53.5' W.**, on the E-W centerline of section 27.

- 40.509** The center 1/4 section corner of section 27.
- 60.829** Point for the center W 1/16 section corner of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
W 1/16  
C          C  
S 27  
2012

Set a steel fence post north of the corner.

From the corner, an improved gravel road, 20 feet wide, extending east and west, bears South, 52.4 links distance.

SUBDIVISION OF SECTION 27,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located in flat, level, open ground, with blackbrush.

**81.149** The 1/4 section corner of sections 27 and 28.

---

From the W 1/16 section corner of sections 27 and 34.

**N. 0°05.7' W.**, on the N-S centerline of the SW 1/4 of section 27.

**40.598** The center W 1/16 section corner of section 27.

---

Subdivision of Section 28,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 28 and 33.

**N. 0°11.0' W.**, on the N-S centerline of section 28.

**40.545** Point for the center 1/4 section corner of section 28, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S28

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush; approximately 75 links distance south of an improved gravel road, 20 feet wide, extending east and west.

**80.858** The 1/4 section corner of sections 21 and 28.

---

From the 1/4 section corner of sections 27 and 28.

**S. 89°45.0' W.**, on the E-W centerline of section 28.

**40.357** The center 1/4 section corner of section 28.

**60.789** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

**80.400** The 1/4 section corner of sections 28 and 29.

SUBDIVISION OF SECTION 29,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

---

Subdivision of Section 29,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 29 and 32.

**N. 0°12.5' W.**, on the N-S centerline of section 29.

- 40.196** Point for the center 1/4 section corner of section 29, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S29

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered tamarisk trees.

- 80.355** The 1/4 section corner of sections 20 and 29.
- 

From the 1/4 section corner of sections 28 and 29.

**N. 89°48.0' W.**, on the E-W centerline of section 29.

- 40.673** The center 1/4 section corner of section 29.

- 80.894** The 1/4 section corner of sections 29 and 30.
- 

Subdivision of Section 30,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 30 and 31.

**N. 0°20.7' E.**, on the N-S centerline of section 30.

- 20.135** Point for the center S 1/16 section corner of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

SUBDIVISION OF SECTION 30,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W  
C  
S 1/16 | S30  
C  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with grasses and blackbrush, west of a two-track road and fence extending northerly and southerly.

- 40.270** Point for the center 1/4 section corner of section 30, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S30  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with low brush, west of a two-track road and fence extending northerly and southerly.

- 60.333** Point for the center N 1/16 section corner of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 1 inch below the ground, magnet at base, with aluminum cap marked

T25S R10W  
C  
N 1/16 | S30  
C  
2012

Set a steel fence post east of the corner, 5 feet distance.

Corner lies 14.5 links distance west of a fence, wood posts and 4-strand barbed-wire, extending north and south, and on the easterly edge of a two-track dirt road.

- 80.396** The 1/4 section corner of sections 19 and 30.

---

From the 1/4 section corner of sections 29 and 30.

SUBDIVISION OF SECTION 30,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

N. 89°54.1' W., on the E-W centerline of section 30.

40.149 The center 1/4 section corner of section 30.

60.309 Point for the center W 1/16 section corner of section 30. Not monumented.

80.732 The 1/4 section corner of sections 25 and 30, on the west boundary of the township, hereinbefore described.

From the N 1/16 section corner of sections 29 and 30.

N. 89°53.4' W., on the E-W centerline of the NE 1/4 of section 30.

40.029 The center N 1/16 section corner of section 30.

From the S 1/16 section corner of sections 29 and 30.

S. 89°59.1' W., on the E-W centerline of the SE 1/4 of section 30.

40.269 The center S 1/16 section corner of section 30.

From the W 1/16 section corner of sections 30 and 31.

N. 0°23.4' E., on the N-S centerline of the SW 1/4 of section 30.

20.175 Point for the SW 1/16 section corner of section 30, at intersection with the E-W centerline of the SW 1/4 of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
SW 1/16 S30  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

40.350 The point for the center W 1/16 section corner of section 30.

From the center S 1/16 section corner of section 30.

S. 89°59.1' W., on the E-W centerline of the SW 1/4 of section 30.

20.177 The SW 1/16 section corner of section 30.

40.607 The point for the S 1/16 section corner of sections 25 and 30, on the west boundary of the township.

SUBDIVISION OF SECTION 30,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the point for the center W 1/16 section corner of section 30.

**N. 0°22.5' E.**, on the N-S centerline of the NW 1/4 of section 30.

- 20.138** Point for the NW 1/16 section corner of section 30, at intersection with the E-W centerline of the NW 1/4 of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
NW 1/16 S30  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered blackbrush.

- 40.276** The W 1/16 section corner of sections 19 and 30.

From the center N 1/16 section corner of section 30.

**N. 89°41.2' W.**, on the E-W centerline of the NW 1/4 of section 30.

- 20.149** The NW 1/16 section corner of section 30.

- 40.560** The N 1/16 section corner of sections 25 and 30, on the west boundary of the township, hereinbefore described.

Subdivision of Section 31,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 6 and 31, on the south boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 2011-12 resurvey, with a rebar alongside the corner, and a steel fence post north of the corner.

**N. 0°17.7' E.**, on the N-S centerline of section 31.

- 20.150** Point for the center S 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked



SUBDIVISION OF SECTION 31,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T25S R10W  
C  
S 1/16 | S31  
C  
2012

Set a steel fence post north of the corner.

From the corner, a fence, wood posts and 3-strand barbed-wire, extending northerly and southerly, bears West, 90.6 links distance.

Corner is located in flat, level, open ground, with scattered blackbrush.

- 40.300** Point for the center 1/4 section corner of section 31, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S31  
2012

Set a steel fence post west of the corner.

Corner is located in flat, level, open ground with scattered brush, in an abandoned fence, wood posts and fallen barbed-wire, extending northerly and southerly.

- 60.452** Point for the center N 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C  
N 1/16 | S31  
C  
2012

Set a steel fence post north of the corner.

From the corner, a fence, wood posts and 4-strand barbed-wire, extending northerly and southerly, bears east, 24.5 links distance.

Corner is located in flat, level, open ground with blackbrush; approximately 30 links east of a two-track dirt road.

SUBDIVISION OF SECTION 31,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

**80.604** The 1/4 section corner of sections 30 and 31.

---

From the 1/4 section corner of sections 31 and 32.

**S. 89°58.9' W.**, on the E-W centerline of section 31.

**20.247** Point for the center E 1/16 section corner of section 31. Not monumented.

**40.494** The center 1/4 section corner of section 31.

**60.741** Point for the center W 1/16 section corner of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

W 1/16  
C          C  
S 31  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**81.110** The 1/4 section corner of sections 31 and 36, on the west boundary of the township, hereinbefore described.

---

From the E 1/16 section corner of sections 6 and 31, on the south boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2011-12 resurvey, with a steel fence post west of the corner.

**N. 0°13.6' E.**, on the N-S centerline of the SE 1/4 of section 31.

**20.170** Point for the SE 1/16 section corner of section 31, at intersection with the E-W centerline of the SE 1/4 of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

SE 1/16 S31  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered rabbitbrush.

SUBDIVISION OF SECTION 31,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

**40.340** The point for the center E 1/16 section corner of section 31.

---

From the point for the S 1/16 section corner of sections 31 and 32.

**N. 89°57.7' W.**, on the E-W centerline of the SE 1/4 of section 31.

**20.273** The SE 1/16 section corner of section 31.

**40.545** The center S 1/16 section corner of section 31.

---

From the W 1/16 section corner of sections 6 and 31, on the south boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 1 inch above the ground, with aluminum cap marked as described in the official record of the 2011-12 resurvey, with a steel fence post west of the corner.

**N. 0°22.3' E.**, on the N-S centerline of the SW 1/4 of section 31.

**20.131** Point for the SW 1/16 section corner of section 31, at intersection with the E-W centerline of the SW 1/4 of section 31.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
SW 1/16 S31  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with scattered low brush.

**40.262** The center W 1/16 section corner of section 31.

---

From the center S 1/16 section corner of section 31.

**N. 89°57.9' W.**, on the E-W centerline of the SW 1/4 of section 31.

**20.275** The SW 1/16 section corner of section 31.

**40.609** The point for the S 1/16 section corner of sections 31 and 36, on the west boundary of the township.

---

From the center W 1/16 section corner of section 31.

**N. 0°22.1' E.**, on the N-S centerline of the NW 1/4 of section 31.

**20.133** Point for the NW 1/16 section corner of section 31, at intersection with the E-W centerline of the NW 1/4 of section 31.

SUBDIVISION OF SECTION 31,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
NW 1/16 S31  
2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

**40.266** The W 1/16 section corner of sections 30 and 31.

From the center N 1/16 section corner of section 31.

**S. 89°55.6' W.**, on the E-W centerline of the NW 1/4 of section 31.

**20.221** The NW 1/16 section corner of section 31.

**40.624** The point for the N 1/16 section corner of sections 31 and 36, on the west boundary of the township.

Subdivision of Section 32,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 5 and 32, on the south boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2011-12 resurvey, with a steel fence post north of the corner.

**N. 0°13.3' W.**, on the N-S centerline of section 32.

**40.059** Point for the center 1/4 section corner of section 32, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C 1/4 S32  
2012

Set a steel fence post north of the corner.

From the corner, the extrapolated intersection point of several abandoned fences, only scattered wood posts and barbed-wire remnants remaining, extending northerly, easterly, and westerly, bears N. 81° W., 18 links distance.

Corner is located in gently-rolling, sandy ground, with blackbrush

SUBDIVISION OF SECTION 32,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

and tamarisk trees.

- 60.269** Point for the center N 1/16 section corner of section 32.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W  
C  
N 1/16 | S32  
C  
2012

Set a steel fence post north of the corner.

Corner lies in low sand dunes.

- 80.479** The 1/4 section corner of sections 29 and 32.

From the 1/4 section corner of sections 32 and 33, perpetuated by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 10 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 32/33 2008 LS 162522, with a wood fence post, 5 inches diameter, projecting 6 ft. above ground, with barbed wire around it, set west of the corner. This position is accepted as a careful and faithful perpetuation of the original corner position.

**N. 89°37.5' W.**, on the E-W centerline of section 32.

- 40.161** The center 1/4 section corner of section 32.

- 80.806** The 1/4 section corner of sections 31 and 32.

From the center N 1/16 section corner of section 32.

**N. 89°39.1' W.**, on the E-W centerline of the NW 1/4 of section 32.

- 40.512** The N 1/16 section corner of sections 31 and 32.

Subdivision of Section 33,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 4 and 33, on the south boundary of the township, hereinbefore described.

**N. 1°00.3' W.**, on the N-S centerline of section 33.

SUBDIVISION OF SECTION 33,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.102** Point for the center 1/4 section corner of section 33, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S33

2012

Set a steel fence post north of the corner.

Corner is located in flat, level ground, with scattered blackbrush.

- 80.470** The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

**S. 89°59.6' W.**, on the E-W centerline of section 33.

- 40.430** The center 1/4 section corner of section 33.

- 60.983** Point for the center W 1/16 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

W 1/16  
C  $\frac{\quad}{\quad}$  C  
S 33

2012

Set a steel fence post north of the corner.

Corner is located in gently-rolling, sandy ground, with scattered blackbrush; west of the westerly Union Pacific Railroad right-of-way fence extending north and south.

- 69.231** Centerline of State Highway No. 257, a paved road, 27 feet wide, bears N. 4° E. and S. 4° W.

- 81.536** The 1/4 section corner of sections 32 and 33.

From the W 1/16 section corner of sections 4 and 33, on the south boundary of the township, hereinbefore described.

**N. 1°08.9' W.**, on the N-S centerline of the SW 1/4 of section 33.

- 40.004** The center W 1/16 section corner of section 33.

SUBDIVISION OF SECTION 33,  
TOWNSHIP 25 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH.

## CHAINS

N. 0°27.3' W., on the N-S centerline of the NW 1/4 of section 33.

40.408 The W 1/16 section corner of sections 28 and 33.

Subdivision of Section 34,  
T. 25 S., R. 10 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 3 and 34, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 13 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 34/3 2008 LS 162522, as described in the official record of the 2011-2012 resurvey.

From the corner, a fenceline, wood post and 4-strand barbed-wire, extends easterly and westerly.

N. 0°38.8' W., on the N-S centerline of section 34.

40.203 Point for the center 1/4 section corner of section 34, at intersection with the E-W centerline.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, magnet at base, with aluminum cap marked

T25S R10W

C 1/4 S34

2012

Set a steel fence post north of the corner.

Corner is located in flat, level, open ground, with blackbrush.

80.333 The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35, reestablished at proportionate position by James D. Edwards, Utah PLS 162522, as shown on "DEPENDENT RESURVEY A PORTION OF T25S, R9 AND 10 WEST, SLM STATE PLANE COORDINATES-UTAH CENTRAL", dated February-March 2008, monumented with an aluminum rod, 1 inch diameter, firmly set, projecting 17 inches above the ground, with aluminum cap, 3 1/4 inches diameter, marked MILLARD COUNTY SURVEY T25S R10W 34/35 2008 LS 162522. There is no remaining evidence of the 1870 wood post. This is accepted as a careful and faithful reestablishment of the original corner.

Set a steel fence post north of the corner.

N. 89°40.8' W., on the E-W centerline of section 34.

40.228 The center 1/4 section corner of section 34.

80.457 The 1/4 section corner of sections 33 and 34.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Phil Freiberg	Survey Technician
Rob Hickman	Survey Aid
Todd Ferrando	Survey Aid

---



## CERTIFICATE OF SURVEY

I, *Scott A. Burkhardt, Cadastral Surveyor*, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the *29<sup>th</sup> day of May, 2012*, I have *dependently resurveyed portions of the south (Fifth Standard Parallel South), east, west, and north boundaries, a portion of the subdivisional lines, and subdivided sections 1, 2, 3, 4, 8, 9, 10, 15, 18, 19, 20, 21, 24, 27, 28, 29, 30, 31, 32, 33, and 34, in Township 25 South, Range 10 West, of the Salt Lake Meridian, in the State of Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

11/25/13

Date

Scott A. Burkhardt

Cadastral Surveyor

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The following field notes of the *dependent resurvey of portions of the south (Fifth Standard Parallel South), east, west, and north boundaries, a portion of the subdivisional lines, and the subdivision of sections 1, 2, 3, 4, 8, 9, 10, 15, 18, 19, 20, 21, 24, 27, 28, 29, 30, 31, 32, 33, and 34, in Township 25 South, Range 10 West, Salt Lake Meridian, Utah*, executed by *Scott A. Burkhardt, Cadastral Surveyor*, having been critically examined and found correct, are hereby approved.

November 29, 2013

Date

Daniel W. Webb

Chief Cadastral Surveyor for Utah